



NEW KID IN TOWN

- Modular cable management
- Supports dual graphic card technology (SLI/CrossFire X)
- Active PFC
- 140mm smart fan with automatic speed
- Green Power efficiency > 72%
- 4 separate 12V lines
- SATA connectors

Form size:	ATX/BTX Standard V2.91
Power:	800W
Input power:	115/230 Vac
	14.5A/7.0A
	Frequency 50/60Hz
Output power:	+3.3V: 24A
	+5V: 32A
	+12V1: 18A
	+12V2: 18A
	+12V3: 20A
	+12V4: 22A
	-12V: 0.5A
	+5VSB: 2.2A

Output connections:	1x 20/24pin MB
	1x 12V 8pin CPU
	1x 12V 4pin CPU
	6x SATA
	8x 4pin peripherals
	2x 6pin PCle
	2x 6+2pin PCle
	1x FDD
PFC:	Active
Cooling:	140mm smart fan with automatic speed
Noise level:	< 21 dBA
Protections:	Over voltage; under voltage; overload; short circuit
Dimensions:	85 (H) x 150 (L) x 163 (D) mm
Extra features:	- Modular cable management
	- Supports dual graphic card (SLI/ CrossFire X)
	- Active PFC
	- 140mm smart fan with auto- matic speed
	- Green Power efficiency > 72%
	- 4 separate 12V lines
	- SATA connectors